



Paddock Slab

MESH STRUCTURE WITH CONNECTION SYSTEM



SPECIFICATIONS

Length	19.69"
Width	15.75"
Height	1.58"
Weight/slab	4.63 lbs
Weight/m ²	23.15 lbs
Coverage/slab	2.15/ft ²
Coverage	5 units = 10.76 ft ²
Items/pallet	200 units
Coverage/pallet	420 ft ²
Material	100% recycled plastic
Connection	T slugs and slots
Color	Black

KEY FACTS

- » Ideal aperture size for horses
- » Excellent water permeation through the surface
- » Durable, non-rotting and weather resistant
- » High stability due to strong web
- » Frost and UV-resistant
- » Low maintenance and cost effective throughout the product life
- » The lightweight interlocking design enables ease and speed of installation
- » Paddock Slab reduces the carbon footprint of a project and it is completely recyclable

Permeable design

Offers excellent water permeation through the surface preventing mud.

Low maintenance

Quick and easy to install.

Load capacity

Suitable for heavy-duty equipment, load class SLW 60, according to DIN1072.

Perfect design

Ideal for horses - smaller cells for hoof support with non-slip ammonia-resistant surface

Ground erosion

Prevents erosion of earth, ideal at gateways and feeding points.

Environmentally friendly

Manufactured from 100% recycled plastic.

Stable

Connection fit improves stability with generous expansion capability.

